

Air injection Vacuum Blower

VT3805.XL

Hibon Ingersoll Rand presents new state-of-the-art technology in three-lobe, positive displacement blowers. This model offers a wide range of design features and incorporates energy efficiency improvements, complying with the strictest operational requirements of a variety of applications. The VTB XL series air-injected, high-vacuum blowers are ideally suited for the rigorous demand of the vacuum truck and industrial vacuum markets. Hibon is a worldwide leader in three-lobe positive displacement blower technology with thousands of units installed around the globe.

Characteristics of the VTB XL Series Blower

- Three-lobe impeller construction
- Unique air injection system
- Increased efficiency
- Clearances adjusted automatically during assembly
- Larger oil capacity
- High volume oil thrower
- High performance sealing arrangement using 4 piston rings

Benefits

- Quieter operation than two-lobe impeller construction
- Allows high vacuum including "dead end" operation without overheating
- No oil or water cooling system (100% oil free air)
- Requires less horsepower for the same performance
- Easier maintenance
- Runs cooler
- Better lubrication of bearings
- Less frequent oil changes

Configurations Better by design

















RH CCW

Configuration	With feet option	Without feet
BS CW	F0145701111	F014570111
LH CW	•	F014570101
TS CW	F0145701211	F014570121
RH CW	•	F014570131
BS CCW	F0145701101	F014570110
LH CCW	•	F014570100
TS CCW	F0145701201	F014570120
RH CCW	•	F014570130

TS CCW Shaft rotation Air flow

Air injection

RH = Right hand shaft

LH = Left hand shaft

BS = Bottom shaft


TS = Top shaft

CW = Clockwise rotation

CCW = Counter clockwise rotation

Performance chart


VOLUME DISPLACEMENT														
Speed (RPM)	9"	HG	12"	HG	15"	HG	18"	HG	21"	HG	24"	HG	27"	HG
RPM	CFM	ВНР	CFM	ВНР										
2600	262	7	250	9	226	11	203	13	171	15	67	17	-	-
2900	297	8	285	10	262	12	240	15	207	17	102	19	-	-
3200	332	9	320	11	299	14	277	16	243	19	137	21	-	-
3500	367	10	355	13	336	15	313	18	279	21	172	23	-	-
3800	402	11	391	14	372	17	350	20	315	23	207	26	-	-
4000	425	12	414	15	397	18	374	21	339	24	231	27	-	-
4200	448	13	437	16	421	19	399	22	363	25	254	28	-	-
4400	471	14	461	17	446	20	423	24	387	27	277	30	24	33
4600	495	14	484	18	470	21	448	25	411	28	301	31	63	35
4800	518	15	508	19	495	22	472	26	435	29	324	33	94 **	38 **



^{**} For intermittent use only. (15 min / hour)



VTB805XL Dimensions



Spare parts

KIT 1 - STANDARD MAINTENANCE KIT	KIT 2 - SET OF RING HOLDERS	Kit 3 - Set of Gears	Кіт 4 - Н еа D Р Lате	HIBON LUBE
No. R014210100	No. R014092100	No. P148502042	No. P145200497	LUBE - 46086567
				When I sh

Ingersoll Rand Industrial Technologies provides products, services and solutions to enhance the efficiency and productivity of our commercial, industrial and process customers. Our innovative products include air compressors, air systems components, tools, pumps, material and fluid handling systems and microturbines. Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialized equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service. Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.



©2013 Ingersoll-Rand Company



Authorized Hibon Distributor, Service & Repair Facility 120 – 10293 276 ST, Acheson, Alberta, Canada T7X 6A5 T: 780.962.1827 F: 780.962.1830 E: sales@fraserwoods.ca www.fraserwoods.ca