

Air injection Vacuum Blower

VTH810.XL

Hibon Ingersoll Rand presents new state-of-the-art technology in three-lobe, positive displacement blowers. This model offers a wide range of design features and incorporates energy efficiency improvements, complying with the strictest operational requirements of a variety of applications. The VTB XL series air-injected, high-vacuum blowers are ideally suited for the rigorous demand of the vacuum truck and industrial vacuum markets. Hibon is a worldwide leader in three-lobe positive displacement blower technology with thousands of units installed around the globe.

Characteristics of the VTB XL Series Blower

- Three-lobe impeller construction
- Unique air injection system
- Increased efficiency
- Clearances adjusted automatically during assembly
- · Larger oil capacity
- High volume oil thrower
- High performance sealing arrangement using 4 piston rings

Benefits

- Quieter operation than two-lobe impeller construction
- Allows high vacuum including "dead end" operation without overheating
- No oil or water cooling system (100% oil free air)
- Requires less horsepower for the same performance
- Easier maintenance
- Runs cooler
- Better lubrication of bearings
- Less frequent oil changes

Better by design

Configurations


















Configuration	With feet option	Without feet
BS CW	F0145701111	F014570111
LH CW	•	F014570101
TS CW	F0145701211	F014570121
RH CW	•	F014570131
BS CCW	F0145701101	F014570110
LH CCW	•	F014570100
TS CCW	F0145701201	F014570120
RH CCW	•	F014570130



Air injection

RH = Right hand shaft LH = Left hand shaft


BS = Bottom shaft

TS = Top shaft CW = Clockwise rotation CCW = Counter clockwise rotation

VOLUME DISPLACEMENT														
Speed (RPM)	9"	HG	12"	HG	15"	HG	18"	HG	21"	HG	24"	HG	27"	' HG
RPM	CFM	ВНР	CFM	ВНР	CFM	ВНР								
2200	573	15	558	18	535	21	503	25	458	29	336	33	97	37
2600	700	18	686	22	665	26	634	31	593	35	478	39	231	44
2800	764	19	750	24	731	28	699	33	661	38	548	42	298	48
3000	827	21	814	26	796	30	765	36	729	41	619	46	365	52
3200	891	22	878	28	861	32	830	39	797	44	690	49	432	56
3400	955	24	942	30	927	35	896	42	864	47	760	53	499	60
3600	1019	26	1007	32	992	38	961	45	932	51	831	56	566**	63**
3800	1082	28	1071	35	1057	40	1027	49	1000	54	902**	60**	_	_



VTB810XL Dimensions



I.D. 4.92 ര Ø8.27 B.C. 4 HOLES 26.44 X M16 00 14.47 3.17 TOP 17.20 8.60 12.99 12.20

FRONT

HORIZONTAL GEARS

- 2. WEIGHT: 344 lbs.
- 3. C.W. SHAFT ROTATION ALSO AVAILABLE ON REQUEST.
- 4. DO NOT USE FOR CONSTRUCTION.

Spare parts

KIT 1 - STANDARD MAINTENANCE KIT	KIT 2 - SET OF RING HOLDERS	Kit 3 - Set of Gears	Кіт 4 - Н еа D Р Lате	HIBON LUBE
No. R015210100	No. R015092100	No. P158502042	No. P155200497	LUBE - 46086567
				When the

Ingersoll Rand Industrial Technologies provides products, services and solutions to enhance the efficiency and productivity of our commercial, industrial and process customers. Our innovative products include air compressors, air systems components, tools, pumps, material and fluid handling systems and microturbines. Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialized equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service. Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation



©2013 Ingersoll-Rand Company



Authorized Hibon Distributor, Service & Repair Facility 120 - 10293 276 ST, Acheson, Alberta, Canada T7X 6A5 T: 780.962.1827 F: 780.962.1830 E: sales@fraserwoods.ca